

Declaration of Performance

N° DoP: 2026-001 SA006

Unique identification code of the product-type:	Corrugated bitumen sheet - Category S : INNOLINE®
Intended Use/es	Discontinuously laid pitched roof coverings for buildings
Manufacturer	Onduline 5-7 rue Frédéric Clavel 92150 Suresnes France
System/S of AVCP	System 3 (reaction to fire) System 4
Harmonised Standard	EN 534:2006 +A1:2010
Notified Body/ies	1488 - Instytut Techniki Budowlanej - Poland

DECLARED PERFORMANCES

Essential Characteristics	Performance	Harmonised standard
Reaction To Fire (Class)	E	EN 534:2006 +A1:2010
External Fire Performance (Class)	NPD*	
Water Impermeability (Pass/Fail)	Pass	
Water Impermeability After Freeze Per Thaw Ageing (Pass/Fail)	Pass	
Bending Under Downward Load (N/m ²)	> 700	
Impact Strength (mm)	250	
Tearing Strength (N)	≥ 150	
Tearing Strength After Freeze/Thaw Ageing (N)	≥ 150	
Thermal Coefficient (1/K)	< 100E-6	

*NPD: No Performance Determined

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above.

Version number: v01

Signed for and on behalf of the manufacturer by:

Grégoire MOREL
Managing Director of Onduline
Suresnes

09/07/2026

